

## Ranger CV Boot Guards

**P/N 10545-ST (STEEL)**

**Fits: 2010-12, 800cc, and 800 Crew Ranger**

**2010-2011, 500 4x4**

**Front are Rear Included**

**Does not fit Ranger HD**

Includes:

Front:

1. (2) Front Guards (RH and LH)
2. (8) Pipe Clamp (45 degree corners)

Rear:

1. (2) Rear Guards (RH and LH)
2. (4) Square Tube Clamps

(16)1/4-20 Flange Head Bolts

(16) Nylon Nuts

Installation:

Front:

Using the Pipe clamps, bolt and nuts attach the guards to the front A-arms. Before tightening check for clearance when you turn the wheel both ways.

Rear:

Using the square clamps and remaining bolts attach the guards to the rear. You will only use two clamps per side. You will use two holes in the outer end of the a-arms for two bolts per guard.



## Ranger CV Boot Guards

**P/N 10545-ST (STEEL)**

**Fits: 2010-12, 800cc, and 800 Crew Ranger**

**2010-2011, 500 4x4**

**Front are Rear Included**

**Does not fit Ranger HD**

Includes:

Front:

1. (2) Front Guards (RH and LH)
2. (8) Pipe Clamp (45 degree corners)

Rear:

1. (2) Rear Guards (RH and LH)
2. (4) Square Tube Clamps

(16)1/4-20 Flange Head Bolts

(16) Nylon Nuts

Installation:

Front:

Using the Pipe clamps, bolt and nuts attach the guards to the front A-arms. Before tightening check for clearance when you turn the wheel both ways.

Rear:

Using the square clamps and remaining bolts attach the guards to the rear. You will only use two clamps per side. You will use two holes in the outer end of the a-arms for two bolts per guard.



## Ranger CV Boot Guards

**P/N 10545-ST (STEEL)**

**Fits: 2010-12, 800cc, and 800 Crew Ranger**

**2010-2011, 500 4x4**

**Front are Rear Included**

**Does not fit Ranger HD**

Includes:

Front:

1. (2) Front Guards (RH and LH)
2. (8) Pipe Clamp (45 degree corners)

Rear:

1. (2) Rear Guards (RH and LH)
2. (4) Square Tube Clamps

(16)1/4-20 Flange Head Bolts

(16) Nylon Nuts

Installation:

Front:

Using the Pipe clamps, bolt and nuts attach the guards to the front A-arms. Before tightening check for clearance when you turn the wheel both ways.

Rear:

Using the square clamps and remaining bolts attach the guards to the rear. You will only use two clamps per side. You will use two holes in the outer end of the a-arms for two bolts per guard.



## Ranger CV Boot Guards

**P/N 10545-ST (STEEL)**

**Fits: 2010-12, 800cc, and 800 Crew Ranger**

**2010-2011, 500 4x4**

**Front are Rear Included**

**Does not fit Ranger HD**

Includes:

Front:

1. (2) Front Guards (RH and LH)
2. (8) Pipe Clamp (45 degree corners)

Rear:

1. (2) Rear Guards (RH and LH)
2. (4) Square Tube Clamps

(16)1/4-20 Flange Head Bolts

(16) Nylon Nuts

Installation:

Front:

Using the Pipe clamps, bolt and nuts attach the guards to the front A-arms. Before tightening check for clearance when you turn the wheel both ways.

Rear:

Using the square clamps and remaining bolts attach the guards to the rear. You will only use two clamps per side. You will use two holes in the outer end of the a-arms for two bolts per guard.

