

RZR Radio Enclosure P/N 10510

Includes:

1. (8) #6 x 1" TEK Screw
2. (4) 1/4-20 x 1/2" Hex Bolt
3. (4) #14 x 1" TEK Screw
4. (6) 1/4-20 x 3/4" Flange Bolt
5. (6) 1/4 Nylon Nut
6. (4) 6-32 Nylon Nut
7. (1) 1/4 Wide Gasket x 5" long
8. (1) Gland Plate
9. (1) Marine Cover
10. (1) Aluminum Box
11. (1) Aluminum Front
12. (2) Aluminum Side Brackets
13. (1) Logo Sticker

Installation:

1. Fasten front panel to the box using the #6 Nylon nuts.
2. Attach the side brackets to the enclosure using the 1/4-20 x 1/2" bolts. Do not tighten yet.
3. Attach the Marine face plate to the enclosure using the #6 self drilling screws. Only use four as pictured.
4. The gasket goes around the gland plate for the rear opening. The plate can be attached using the remaining #6 self tapping screws after your radio is installed.
5. Attach the side brackets under your dash with the 1/4-20 x 3/4" bolts or large self drilling screws. There may already be existing holes in your frame.
6. Attach the front panel to the metal strap behind the plastic with 1/4-20 x 3/4" bolts and Nylon nuts.

