

## Kawasaki Mule Flip up windshield P/N 9653

### Includes:

- (1) Large Upper windshield
- (1) Small Lower Windshield
- (6) 10-32x3/4" Truss Hd Screw (91770A831)
- (6) 10-32 Nylon Nut (90631A411)
- (12) #10 Rubber Washer (BR90130A012)
- (1) Strips 11.75 long (hook and loop)
- (6) Steel Loop Strap (BR8863T22)
- (1) Plastic Hinge
- (2) Velcro "One Wrap" 12" long (94905K63)

### Installation:

1. Install hinge to windshield. The offset should go towards the front. Check to make sure the hinge will flip up towards the front before attaching to windshield. Use a rubber mallet and soapy water to install hinge.
2. Using the steel straps, screws, rubber washers and nuts attach the windshield to the rail cage. The rubber washers should sandwich the windshield to protect the windshield from over tightening.
3. Use the "hood and loop" adhesive backed Velcro to attach the bottom of the windshield to the hood. Stick it to the flange on the bottom of the windshield and then stick to the hood.
4. Use the Velcro "one wrap" to secure the bottom windshield to the rail cage as pictured.

**Warning:** Always remove windshield when driving on the street or when trailering Mule on the street. Serious injury or death could result used on the road or highway.



Extreme Metal Products, LLC  
1-216-267-5335  
Www.extrememetalproducts.com

